



PRODUCT CATALOGUE

Providing engineering, construction, and supply chain solutions to a global market.

CONTENTS

| Construction Materials & Chemicals | 1 |
|---------------------------------------|---|
| Rebar Spacer Technology & Accessories | 2-4 |
| Rebar Fixing | 5 |
| Formwork Technology & Accessories | 6-9 |
| Rebar Processing & Fabrication | 10-11 |
| Construction Accessories | 12-16 |
| Damp Course & Waterproofing | 17-20 |
| Our Clients | 21 |
| Contact Information | 22 |
| | Rebar Fixing Formwork Technology & Accessories Rebar Processing & Fabrication Construction Accessories Damp Course & Waterproofing Our Clients |



CONSTRUCTION MATERIALS & CHEMICALS

Kertus Group has developed a winning formula in Supply Chain and Logistics Management which has become the strategic cornerstone of our competitive advantage.

The supply division was established to benefit from emerging integrated logistic opportunities; simultaneously reducing costs and increasing customer service levels. Whilst our key value is our ability to integrate supply chain, our core supply capabilities include all traditional logistics functions from Inventory Optimisation to Transportation.

Our scope includes, but is not limited to:

- Rebar Spacer Technology & Accessories
- Cement Spacers / Cover Blocks
- Rebar Chair Spacers
- Bone Spacers
- Rebar Safety Caps
- Centralisers
- Rebar Fixing
- Knipex Rebar Fixing Pliers
- Binding Wire
- Formwork Technology & Accessories
- Ferrule Tubing / Tie-Rod Sleeves
- Push-On Cones / Ferrule Tube Cones
- Permanent Push-On Cones / Ferrule Tube Cones
- Screw-On Cones
- Shutter Foam
- Shutter Tape
- Discontinuous Thread DYWIDAG Tie Rods

- Rebar Processing and Fabrication
- Manual Rebar Cutters / Benders
- Shutter Buttons and Plugs
- Construction Accessories
- Step Irons
- Yellow & Orange Barrier Netting
- Orange Safety Netting
- Brick Force
- Galvanised Butterfly Ties
- Galvanised Wall Ties
- Hoop Iron
- Damp Course & Waterproofing
- Waterproofing Membrane
- Damp Course SABS DPC 375 micron

CHEMICAL BRANDS












REBAR SPACER TECHNOLOGY & ACCESSORIES

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.


CEMENT SPACERS / COVER BLOCKS

Certified strength to withstand extreme rebar weights or pressure. Embedded fixing wire for easy fixing to rebar. Quick and easy to install.



| Cement Spacers Square | | | |
|--|--------------------------------------|---------------------------------|---------------------------------|
| Code | Cover mm | Rebar mm | Units per bag |
| CS-25S CS-30S CS-35S CS-40S CS-50S | 25mm 30mm 35mm 40mm 50mm | any any any any any | 250 250 250 200 200 |

*Square base to ensure best support without tipping or falling over.



| Cement Round Spacers | | | |
|--|--------------------------------------|---------------------------------|---------------------------------|
| Code | Cover mm | Rebar mm | Units per bag |
| CS-25S CS-30S CS-35S CS-40S CS-50S | 25mm 30mm 35mm 40mm 50mm | any any any any any | 250 250 250 200 200 |

*Round base for minimum contact with the shutter.



REBAR SPACER TECHNOLOGY & ACCESSORIES

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

REBAR CHAIR SPACERS

Rebar Chair Spacers are used to support rebar on a deck, which includes radial grounding, heavy duty rebar laying and beams. The wide base of these rebar chair spacers prevent the chairs from tipping over. These rebar chair spacers can be secured to the rebar by clipping them over the rebar.



| Chair Spacers / Cover Blocks | | | | |
|--|-------------|--------------------------------------|---|-----------------------------------|
| Code | | Cover mm | Rebar mm | Units per bag |
| CS-NT-20 CS-NT-20 CS-NT-30 CS-NT-40 CS-NT-50 | 5 D D | 20mm 25mm 30mm 40mm 50mm | 8 to 25mm 8 to 25mm 8 to 25mm 8 to 25mm 8 to 25mm | 1000 1000 750 600 500 |

BONE SPACERS

Our fibre concrete Bone spacers or cover blocks are mode using a concrete compression process, which makes them extremely strong. Our Bone spacers are strong enough to withstand extreme rebar weights or pressure. Includes fixing wire for easy fixing to rebar. Quick and easy to install. Our Bone spacers are manufactured at our factory in Midrand.



| Product Code | Product Description | Cover | Units per bag |
|--------------|--------------------------|---------------|------------------|
| FCB30 | Bone spacers 20/25/30 | 20/25/30mm | 200 |
| FCB50 | Bone spacers 35/40/45/50 | 35/40/45/50mm | 200 |

Solid base to ensure best support without tipping or falling over.




REBAR SPACER TECHNOLOGY & ACCESSORIES

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

REBAR SAFETY CAPS

Our Rebar Safety Caps can be used to alert construction workers to the danger of being pierced by protruding rebar.

The minimal cost of using rebar safety caps on a construction site is insignificant compared to lost man hours that may result from injuries. Using our rebar safety caps is a small price to pay for the safety of workers on site.



CENTRALISERS

RMCS Rebar centralisers are used to centralise steel reinforcing in the centre of a pile or can be used to keep stress cables from touching a surface. These entralisers provide a cover of 30mm and will accept rebar up to a size of 25mm.



| Centralisers | | | |
|--------------|----------|------------|---------------|
| Code | Cover mm | Rebar mm | Units per bag |
| CENT25 | 30mm | Up to 25mm | 250 |



REBAR FIXING

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

KNIPEX REBAR FIXING PLIERS

The Knipex Fixing Pliers are the best pliers for rebar fixing on the market today. They are robust and durable and are the most preferred rebar fixing pliers in the contruction industry today. The main application for the Knipex Fixing Pliers is twisting and cutting off tie wire when fixing the rebar.



BINDING WIRE

Our 1,6mm black annealed wire come in 50 kilogram rolls.





Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

FERRULE TUBING / TIE-ROD SLEEVES

Ferrule Tubing or Tie-rod sleeves are used to space shutters and to recover expensive concrete shutter tie-rods. The inside diameter of the ferrule tube needs to be at least 1mm greater than that of the tie-rod.



| Code | Inside Dia | Outside Dia | Lengths |
|---------|------------|-------------|----------|
| F-17-20 | 17mm | 20mm | 3 Meters |
| F-22-25 | 22mm | 25mm | 3 Meters |
| F-26-30 | 26mm | 30mm | 3 Meters |

PUSH-ON CONES / FERRULE TUBE CONES

Ferrule Tube Push-on Cones are used as ends on Ferrule Tubes (Tie-rod sleeves). Fits on the inside of the Ferrule Tube (Tie-rod sleeve). Can be removed after the shutters have been dismantled and be used again.



| Push | -on / Ferrule | Tube Cones | |
|----------|---------------|-------------------|---------------|
| Code | For IDmm | For OD mm | Units per bag |
| EC-17-25 | 17mm | 20mm | 2,000 |
| EC-22-25 | 22mm | 25mm | 1,000 |
| EC-26-30 | 26mm | 30mm | 1,000 |



Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

PERMANENT PUSH-ON CONES / FERRULE TUBE CONES

Permanent Cones are used to hide holes created in the concrete by tie-rods. The cone is fitted to the end of the ferrule tube when the shutters are installed. When the shutters are removed, a plug is inserted to cover the hole, resulting in a flat finish on the concrete. They are made from a durable plastic and are UV protected.



| | Permane | nt Cones | |
|----------|-----------|-----------|---------------|
| Code | For ID mm | For OD mm | Units per bag |
| PC-22-25 | 22mm | 25mm | 1,000 |

SCREW-ON CONES

Screw-on cones have an internal thread and are used together with a rawl tie. They are made from durable hard plastic and can be used several times.



| | Screw-on Cones | |
|------|----------------|---------------|
| Code | Size | Units per bag |
| PC38 | 38mm | 500 |



Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

SHUTTER FOAM

Used for prevention of grout loss through joints in metal or wooden formwork. Self-adhesive backing makes our foam seal easy and clean to use. Water based acrylic adhesive makes our shutter foam easy to remove.



| Shutter Seal | | |
|--------------|-------------|------------|
| Code | Size | Roll Size |
| WS10x20 | 10mm x 20mm | 100 Meters |

SHUTTER TAPE

Shutter Tape is a PVC tape used for the sealing of joints in formwork to prevent grout loss.



| Shutter Tape | | | |
|--------------|------|-----------|--|
| Code | Size | Roll Size | |
| ST50 | 50mm | 30 Meters | |



Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

DISCONTINUOUS THREAD DYWIDAG TIE RODS

Galvanised Combi/Wing Nuts for Formwork

Weldable Formwork 15/17 Discontinuous Thread Dywidag Tie Rods or tiebars are used in construction to tie the formwork together. Combi nuts or Tie nuts are screwed on to the tie rods, to keep the formwork in place.Our Dywidag tie rods have a discontinuous thread and is therefore a self cleansing tie rod.

Concrete is removed from the rod, when the tie nut is removed from the tie rod. We will cut to length on request.



| Tie-Rods with Discontinuous Thread | | | | | | | | | | |
|------------------------------------|---------------------------------|----------------------------------|--|--|--|--|--|--|--|--|
| Code | Size | Lenghts | | | | | | | | |
| DWTR15 DWTR20 DWTR26 | 15/17mm 20/23mm 26,5/31mm | 6 Meters 6 Meters 6 Meters | | | | | | | | |

* Also referred to as "DYWIDAG standard" tie rod



REBAR PROCESSING & FABRICATION

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

MANUAL REBAR CUTTERS / BENDERS

Our manual rebar cutter / benders feature drop-forged high grade alloy tool steel blades with special heat-treatment. Cuts rebar safely, cleanly and efficiently with minimal effort. Bends rebar up to 180 degrees with versatile operation. Can be bolted to floor or board for easy operation. Cutting and bending head can be bought and replaced separately. There are two models available.



| Manual Rebar Cutter/Benders | | | | | | | | | | |
|-----------------------------|------------------|--------------|------------------|--|--|--|--|--|--|--|
| Code Length Capacity Weigh | | | | | | | | | | |
| RC13-BNR RC16-BNR | 1070mm 1320mm | 12mm 16mm | 10.5kgs 16kgs | | | | | | | |



REBAR PROCESSING & FABRICATION

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

SHUTTER BUTTONS AND PLUGS

Shutter Buttons and plugs are used to plug unused tie-rod holes in steel or wooden shutters. This stops the bleeding of concrete through the unused holes in the shutter. Easy to install, just tap it into the hole with a hammer.



| Code | Size | Unit per bag | | |
|---------|--------------|--------------|--|--|
| SB14 | 14mm | 1,000 | | |
| SB16 | 16mm | 1,000 | | |
| SB18 | 18mm | 1,000 | | |
| SB21 | 21mm | 1,000 | | |
| SB21-26 | 21mm to 26mm | 1,000 | | |



| S | hutter Buttons Vario | 0 |
|-----------|----------------------|--------------|
| Code | Size | Unit per bag |
| SB20-25mm | 20 to 25mm | 1,000 |

*Designed to fit into various hole sizes



| | Shutter Board Plugs | |
|---------|---------------------|--------------|
| Code | Size | Unit per bag |
| SP21-22 | 21 to 22mm | 1,000 |
| SP25-26 | 25 to 26mm | 1,000 |

*Designed to plug wooden shutters



Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

STEP IRONS

For use in sewer and drainage manholes or pits. Our step irons are manufactured from high strength steel bar and are fully encapsulated in tough yellow polypropylene for visibility underground. There are no sharp edges or corners on these step irons and the 25mm sides stop feet slipping off.

Our step irons are resistant to corrosion from acids, alkalis and chemicals. Load strength is greater than 3.6kn and they have a pull-out strength of 1.8kn. They can be set into pre-cast structures during concrete pour, caulked into a drilled hole with epoxy resin or fixed with quick setting cement.

| | Step Irons | | | | | | | | | | | |
|---------|-------------|-------|--------|-----------|--|--|--|--|--|--|--|--|
| Product | Product | Width | Length | Thread | | | | | | | | |
| Code | Application | mm | mm | Length mm | | | | | | | | |
| SI1 | Brickwork | 150mm | 185mm | 70mm | | | | | | | | |
| SI2 | Concrete | 150mm | 185mm | 50mm | | | | | | | | |
| SI3 | Fibre | 150mm | 160mm | 30mm | | | | | | | | |





Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

YELLOW & ORANGE BARRIER NETTING

Top Quality Barrier Netting (1 Meter high x 50 Meter long)

RMCS supplies top quality yellow & orange barrier netting for a wide range of applications in the construction industry. Our well weaved for extra strength barrier netting has the following characeristics:



- drawstrings for easy attachement to stakes
- bright orange and yellow for clear visability
- colour fast UV protection- flexible and durable

1020040000

1111111

- flameproof and chemical resistant

| Product Code | Description |
|--------------|--|
| SN-1300H | Orange safety fencing 1 meter high -100 gram per square meter - price per 50 meter roll |

ORANGE SAFTEY NETTING

Top Quality Orange Safety Netting (1m or 1,2m high x 50 Meter long)

RMCS supplies top quality orange saftey netting for a qide range of applications in the contruction industry. Our well manufactured, extra strong and visible orange safety netting is used in numerous applications all over South Africa, such as:

| | | a | t, | 2 | è | ŝ | ÷ | h | | | e. | ł | à | | | 4 | 4 | 1 | 5 | | 5 | 2 | 2 | 2 |
|-----|----|----|----|---|---|---|---|---|---|---|----|---|---|---|---|---|---|-----|----|----|---|---|---|---|
| - | ÷ | ÷ | ę | | - | - | ÷ | ÷ | 1 | | | | ł | | 1 | F | 2 | | | P | ÷ | ÷ | ę | ę |
| | t | t | 1 | | 7 | | | T | I | | | | I | I | 1 | | | r i | r | t | Ť | t | Ť | Ť |
| 1 | t | 1 | 1 | | | | L | Ī | 1 | | | Г | I | 1 | | 1 | | | Г | t | t | t | t | Ť |
| 0 | t | 1 | 1 | T | C | I | ľ | 1 | | 5 | Ľ | Γ | I | 1 | | | | | | h | t | t | t | t |
| 11 | | | 1 | t | ſ | T | Ī | I | | C | E | Γ | I | 1 | | | | | | T. | t | t | t | t |
| U | | F. | r | t | t | I | I | 1 | | Ŀ | L | I | I | 1 | | | | | | | Ľ | t | t | t |
| C | Г | | t | t | 1 | 1 | 1 | | | L | I. | I | I | | | | | E | E. | | | t | t | Ŀ |
| C | Г | г | I | I | 1 | 1 | 4 | | L | Ļ | L | 1 | I | 1 | | | | | Ľ | | 0 | | T | h |
| 1 | I | I | I | 1 | | 4 | 4 | H | Ļ | ł | ŧ | Ŧ | 1 | | | L | L | | | | | E | | |
| 1 | ł, | 1 | 1 | | 2 | - | H | H | ł | ŧ | ÷ | 4 | 4 | 2 | | Ļ | Ļ | H | L | | | | | |
| - } | 4 | 4 | - | | | H | ۲ | ł | ŧ | ł | ÷ | 4 | 4 | | H | ł | ł | H | Ļ. | | - | H | | |
| - 1 | H | + | H | H | ł | t | t | t | t | 1 | 1 | 1 | 1 | 1 | ۲ | t | t | t | t | H | H | Н | Н | |
| | H | H | H | ۲ | t | t | t | T | 1 | 1 | 1 | | | | t | r | t | t | t | | | | H | - |

- Constructions sites
- Works sites
- Open excavations
- Sport events- Catwalks
- Crowd control and
- Restircted areas.

| Product Code | Description |
|--------------|--|
| SN-1200H | Orange safety fencing 1.2 meter high -100 gram per square meter - price per 50 meter roll |



Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

BRICK FORCE

Brickforce is the steel reinforcing that strengthens a wall. It is placed in the cement between a course of bricks. Brickforce is used in every course of the foundations and every course above lintol height (2140mm). Otherwise brickforce is used every fourth course in between the foundations and lintol height or a concrete slab and lintol height.



| | Brick Force | | | | | | | | | | |
|--|---|---|--|--|--|--|--|--|--|--|--|
| Product Code | Width mm | Wire Size mm | Roll Weight | | | | | | | | |
| BF75-20 BF110-20 BF150-20 BF230-20 BF75-28 BF150-28 BF150-28 BF230-28 | 75mm 110mm 150mm 230mm 75mm 150mm 230mm | 2mm 2mm 2mm 2.8mm 2.8mm 2.8mm 2.8mm | 20 kgs 20 kgs 20 kgs 20 kgs 20 kgs 20 kgs 20 kgs 20 kgs | | | | | | | | |



Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

GALVANISED BUTTERFLY TIES

Butterfly Ties are used in general to reinforce house and building walls. Approximately 3 to 4 must be ised per square meter. The central twist in the galvanised butterfly tie, is to prevent moist from travelling across the cavity. The twist mus be placed down in the cavity.

The length of the butterfly tie must be at least 20mm less than the total wall thickness.





| Ga | alvanised B | utterfly Ties | |
|-----------------|--------------------|---------------------|----------------|
| Product Code | Total length mm | Wire Diameter mm | Bundle Size |
| BT18025 | 180mm | 2.5mm | 25 |
| BT20025 | 200mm | 2.5mm | 25 |
| BT22525 | 225mm | 2.5mm | 25 |
| BT25025 | 250mm | 2.5mm | 25 |
| BT32525 | 325mm | 2.5mm | 25 |
| BT200315 | 200mm | 3.15mm | 25 |
| BT225315 | 225mm | 3.15mm | 25 |
| BT250315 | 250mm | 3.15mm | 25 |
| BT180315 | 180mm | 3.15mm | 25 |
| BT275315 | 275mm | 3.15mm | 25 |
| BT300315 | 300mm | 3.15mm | 20 |
| BT350315 | 350mm | 3.15mm | 20 |
| BT380315 | 380mm | 3.15mm | 20 |
| BT400315 | 400mm | 3.15mm | 20 |
| BT500315 | 500mm | 3.15mm | 20 |
| BT530315 | 530mm | 3.15mm | 20 |

GALVANISED WALL TIES



| Ga | Galvanised Wall Ties | | | | | | | | | | | |
|---|---|--|---|--|--|--|--|--|--|--|--|--|
| Product | Total | Wire | Bundle | | | | | | | | | |
| Code | length mm | Diameter mm | Size | | | | | | | | | |
| WT18025 WT22525 WT27525 WT32525 WT225315 WT275315 WT30315 WT325315 WT340315 WT375315 WT380315 WT380315 WT400315 | 180mm 225mm 275mm 325mm 275mm 300mm 325mm 340mm 375mm 380mm 400mm | 2.5mm 2.5mm 2.5mm 2.5mm 3.15mm 3.15mm 3.15mm 3.15mm 3.15mm 3.15mm 3.15mm 3.15mm | 25 25 25 25 25 25 25 25 25 25 25 25 25 2 | | | | | | | | | |
| WT500315 | 500mm | 3.15mm | 25 | | | | | | | | | |
| WT600315 | 600mm | 3.15mm | 25 | | | | | | | | | |



Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

HOOP IRON

Our Hoop Iron is manufactured from SABS-quality galvanised steel of varying thickness depending on individual needs or architects specifications. Hoop Iron is mainly used to brace trusses and to secure trusses to the top of the wall of a structure, but it may also be used for various other applications in the building & construction industry, such as:



- 1. Casting Hoop Iron into a structure during concrete pour,
- 2. Caulking Hoop Iron into a drilled hole with epoxy resin or
- 3. Fixing Hoop Iron with quick setting cement.

Our galvanised Hoop Iron is resistant to corrosion from acids, alkalis and chemicals. The load strength of our Hoop Iron is greater than 3.6kn and they have a pull-out strength of 1.8kn.

| Hoop Iron | | | | | | |
|-----------------|------------------------|-------|-----------|----------------------|--|--|
| Product Code | Product Description | Width | Thickness | Weight per roll | | |
| Hoop Iron 3212 | Hoop iron 32mm x 1.2mm | 32mm | 1.2mm | from 19,7 to 20kgs | | |
| Hoop Iron 3216 | Hoop iron 32mm x 1.6mm | 32mm | 1.6mm | from 25,3 to 25,6kgs | | |



DAMP COURSE & WATERPROOFING

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

WATERPROOFING MEMBRANE

Practically all building materials absorb water. In reality water is the single most damaging cause of structural decay. Rising damp is responsible for more building maintenance costs thanany other cause. This should not and need not be a problem is our Waterproofing is installed between the ground and your slabs.





| Waterproofing Membrane - SABS Black 250 micron | | | | | | |
|--|--|---|---|---|--|--|
| Product Code | Meters per roll | Roll width | Weight Kilograms | SQM per roll | | |
| 10000 10005 10006 10008 10010 10014 10016 10017 145000 145055 | 30 5 10 15 30 15 10 5 30 30 | 1 meter 2 meters 2 meters 3 meters 2 meters 2 meters 2 meters 3 meters 4 meters | 6,92 2,3 4,61 6,92 13,84 10,38 6,92 3,46 20,76 27,69 | 30 10 20 30 90 30 20 10 90 120 | | |
| 145155 | 30 | 6 meters | 41,53 | 180 | | |

DAMP COURSE & WATERPROOFING

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

WATERPROOFING MEMBRANE





| Waterproofing Membrane - SABS Hyperlastic orange 500 micron | | | Waterproofu | ng Membrane - | SABS Hyper | lastic orange 1 | 000 micron | | |
|---|--------------------|---------------------------------|-------------------------|------------------|-----------------|--------------------|---------------------|---------------------|-----------------|
| Product Code | Meters per roll | Roll width | Weight Kilograms | SQM per roll | Product Code | Meters per roll | Roll width | Weight Kilograms | SQM per roll |
| 14000 14005 14015 | 30 30 30 | 3 meter 4 meters 6 meters | 41,53 55,38 83,07 | 90 120 180 | 14050 14100 | 30 30 | 3 meter 4 meters | 83,07 110,76 | 90 120 |

| Waterpro | Waterproofing Membrane - SABS Green 250 micron | | | | | | |
|--|--|----------------------------------|-------------------------|------------------|--|--|--|
| Product Meters Roll Weight SQ Code per roll width Kilograms per | | | | | | | |
| 14500 14505 14515 | 30 30 30 | 3 meters 4 meters 6 meters | 20,76 27,69 41,53 | 90 120 180 | | | |



DAMP COURSE & WATERPROOFING

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

WATERPROOFING MEMBRANE

Used for prevention of grout loss through joints in metal or wooden formwork. Self-adhesive backing makes our foam seal easy and clean to use. Water based acrylic adhesive makes our shutter foam easy to remove.

| Waterproofing Membrane - SABS Black 150 micron | | | | | Waterpro | ofing Memb | orane - SAI | BS Black 150 |) micron |
|--|----------------------------------|---|--|------------------------------|---|----------------------------------|---|---|------------------------------|
| Product Code | Meters per roll | Roll width | Weight Kilograms | SQM per roll | Product Code | Meters per roll | Roll width | Weight Kilograms | SQM per roll |
| 10050 10505 10510 10515 10525 | 30 30 30 30 30 30 | 1 meter 2 meters 3 meters 4 meters 6 meters | 2,77 5,53 8,29 11,06 16.59 | 30 60 90 120 180 | 10550 10560 10565 10570 10580 | 30 30 30 30 30 30 | 1 meter 2 meters 3 meters 4 meters 6 meters | 4,15 8,30 12,46 15,61 24,93 | 30 60 90 120 180 |

| Waterproofing Membrane - SABS Hyperlastic orange 375 micron | | | | | | |
|---|----------|----------|-----------|----------|--|--|
| Product | Meters | Roll | Weight | SQM | | |
| Code | per roll | width | Kilograms | per roll | | |
| 13530 | 30 | 3 meter | 31,15 | 90 | | |
| 13535 | 30 | 4 meters | 41,53 | 120 | | |
| 13540 | 30 | 6 meters | 62,3 | 180 | | |

| | Waterproofing Membrane - SABS Black 500 micron | | | | | | |
|---|--|----------------|---------------------------------|-------------------------|------------------|--|--|
| Product Code Meters per roll Roll width Weight Kilograms SQN per r | | | | | | | |
| | 10650 10655 10660 | 30 30 30 | 3 meter 4 meters 6 meters | 41,63 66,38 83,07 | 90 120 180 | | |

| Waterproofing Membrane - SABS Black Drop sheets 70 micron | | | | | | | |
|---|---------------------------------|--|--|--|--|--|--|
| Product Code | Meters per roll | Roll width | Weight Kilograms | SQM per roll | | | |
| 10680 10682 10684 10690 10692 10694 10707 | 15 10 5 10 15 15 | 2 meters 2 meters 2 meters 3 meters 3 meters 3 meters 4 meters | 1,94 1,29 0,54 0,97 1,94 2,91 3,87 | 30 20 10 15 30 45 60 | | | |



DAMP COURSE & WATERPROOFING

Our top quality products at competitive prices, combined with our excellent service, offer a number one solution for you.

DAMP COURSE - SABS DPC 375 micron

Practically all building materials absorb water. This should not and need not be a problem. In reality water is the single most damaging cause of structural decay. Rising Damp is responsible for more building maintenance costs than any other cause. Prevent rising damp from damaging your building by using our damp course.



| Waterproofing Membrane - SABS Black 100 micron | | | | | | |
|--|----------|------------|-----------|----------|--|--|
| Product | Meters | Roll | Weight | SQM | | |
| Code | per roll | width | Kilograms | per roll | | |
| 11000 | 40 | 4.4 meters | 62.0 | 110.0 | | |
| 11005 | 40 | 150mm | 2.07 | 6.0 | | |
| 11011 | 40 | 225mm | 3.11 | 9.0 | | |
| 11020 | 40 | 340mm | 4.70 | 13.6 | | |
| 11025 | 40 | 450mm | 6.23 | 18.0 | | |

OUR CLIENTS

FLUOR Vopak







www.kertusgroup.co.za



CONTACT INFORMATION

Durban

220 Marine Drive Bluff Durban 4052

Johannesburg

Unit 31 Bridgeway Business Park 434 Sam Green Road Rietfontein 1401

Jody Augustus - Operations Director 073 352 9170 | jody@kertusgroup.co.za

Kamashen Naicker - Commercial Director 072 440 9446 | kamashen@kertusgroup.co.za

Administration 011 872 8114 info@kertusgroup.co.za

www.kertusgroup.co.za





www.kertusgroup.co.za